



CROS Styletto AX

Technical Data



Data sheet also applicable for CROS Styletto sDemo DAX

CROS Styletto AX | Features and Accessories

Style specific features

Ingress Protection Rating	IP68
Nanocoated housing	—
RoHS	✓

Battery specifications

Battery type	Lithium-ion
Battery runtime	up to 23 h
Styletto AX Charger / D&C Charger slimRIC	Mandatory

Cellphone Compatibility

Microphone mode	0.65 – 0.96 GHz 1.4 – 2.7 GHz
-----------------	----------------------------------

✓ available — not available ○ optional

CROS Styletto AX | Further information


Standards and additional information

- ▶ All Cellphone Compatibility measurements were performed according to IEC 60118-13:2019, EN IEC 60118-13:2020 and ANSI C63.19-2019.
- ▶ Cellphone Compatibility definition: It is expected that the hearing aid user can effectively use a compliant wireless device held in a talking position at the ear. Maximum achievable Cellphone Compatibility range: 0.65 – 0.96 GHz and 1.4 – 2.7 GHz.
- ▶ The current consumption is measured in normal operating mode (audio link using e2e wireless 4.0). Due to the settling behaviour of hearing aids, the battery current is measured 3 minutes after turning on.
- ▶ The battery runtime is based on the given current consumption. The actual battery runtime is determined by battery quality, usage and activated feature set.
- ▶ Note: due to the design of the CROS Styletto AX, not all earwear connections will fit inside Styletto AX Charger. Please consult the datasheet Styletto AX Charger for relevant technical information.

Special note for instruments with built-in lithium-ion rechargeable battery

- ▶ The runtime of all lithium-ion rechargeable batteries reduces over time. The estimates are based on fresh lithium-ion rechargeable battery capacity. Under normal operating conditions, the battery will retain up to 80 % of its initial capacity after 2 years of use. Please note that battery performance will vary depending on individual usage patterns and environmental conditions.

The information in this document contains general descriptions of the technical options available, which do not always have to be present in individual cases and are subject to change without prior notice. The required features should therefore be specified in each individual case at the time of conclusion of the respective contract.

 **Legal Manufacturer**
WSAUD A/S
Nymøllevej 6
3540 Lyngø
Denmark


0123

Order No. 04741-99T01-7600
© 06.2021, WSAUD A/S
All rights reserved

Subject to change
without prior notice



WARNING

Choking hazard posed by small parts.

- ▶ This instrument is not intended for the fitting of infants, children under 3 years or persons of mental incapacity.