

## **CROS Pure C&G AX**

**Technical Data** 



## CROS Pure C&G AX | Features and Accessories

Style specific features	
Ingress Protection Rating	IP68
Nanocoated housing	<b>√</b>
RoHS	✓
<b>Battery Specifications</b>	
Battery type	Li-ion
Battery runtime	up to 29 h
Charger RIC / D&C Charger RIC / Portable Charger RIC	Mandatory
Cellphone Compatibility	
Microphone mode	0.65 - 0.96 GHz 1.4 - 2.7 GHz
	✓ available — not available O option

## Standards and additional information

- ▶ The current consumption is measured in normal operating mode (audio link using e2e wireless 4.0). Due to the settling behaviour of hearing aids, the battery current is measured 3 minutes after turning on.
- ▶ The battery runtime is based on the given current consumption. The actual battery runtime is determined by battery quality, usage and activated feature set.
- ▶ All Cellphone Compatibility measurements were performed according to IEC 60118-13:2019, EN IEC 60118-13:2020 and ANSI C63.19-2019.
- ▶ Cellphone Compatibility definition: It is expected that the hearing aid user can effectively use a compliant wireless device held in a talking position at the ear. Maximum achievable Cellphone Compatibility range: 0.65 – 0.96 GHz and 1.4 – 2.7 GHz.

The information in this document contains general descriptions of the technical options available, which do not always have to be present in individual cases and are subject to change without prior notice. The required features should therefore be specified in each individual case at the time of conclusion of the respective contract.

Legal Manufacturer WSAUD A/S Nymøllevej 6 3540 Lynge Denmark

Order No. 04615-99T01-7600 © 03.2021, WSAUD A/S All rights reserved

Subject to change without prior notice



## **⚠** WARNING

Choking hazard posed by small parts.

▶ This instrument is not intended for the fitting of infants, children under 3 years or persons of mental incapacity.